


Single-leaf door system with oculus in aluminum with thermal break, with handle locking system.



### Configurations



### Technical features

- Thermal Break Aluminum Extruded Profiles
- Construction depth of frame 75 mm
- Construction depth of leaf 75 mm
- EPDM tightness packing (DIN 6873)
- Glass thickness up to a 55 mm
- Serratura con cilindro europeo
- It can be installed on panels of any thickness through the usage of adaptable counter-frames systems.





**CE** Marchio CE  
in accordance with UNI EN 14351-1

### Performance\*

- |  |   |
|--|---|
| <p><b>2</b><br/>Air permeability<br/>Classe 2 in accordance with<br/>UNI EN 12207</p>  | <p><b>C2</b><br/>Wind load resistance<br/>Classe C2 in accordance with<br/>UNI EN 12211</p> |
| <p><b>U<sub>w</sub> 1,4</b><br/>Thermal insulation<br/>U<sub>w</sub> = 1,4 W/m<sup>2</sup>K (U<sub>g</sub> = 1 W/m<sup>2</sup>K con cana-<br/>lina warm edge dim. rif. 1100 x 2200 mm)<br/>in accordance with UNI EN 10077-1</p> | <p><b>3A</b><br/>Watertight seal<br/>Classe 5A in accordance with<br/>UNI EN 12208</p>      |

\*Values are obtained on a window / door with dim. ref. 1100 x 2200 mm  
\*All the values reported are from a notified body

### Intended use

- |   |   |   |
|---|---|---|
|  Healthcare Buildings |  Educational Buildings |  Business Buildings    |
|  Commercial Buildings |  Industrial Buildings  |  Residential Buildings |

### Options

- |  |   |   |   |
|--|---|---|---|
|  Different RAL paint coating |  Anta con pannello isolante sandwich |  Shatter-proof glass                     |  Security and/or electric lock |
|  Panic exit bar              |  Door closer arm                     |  Protective and/or ventilation grating |   |